


Solar Garden Light



Original design, patent appearance

WE ARE A PROFESSIONAL MANUFACTURER OF LED GAMDEN LIGHT,
OUR COMPANY MAINLY PRODUCE OUTDOOR SOLAR GARDEN LIGHT,
SUCH AS SOLAR WALL LIGHT,SOLAR PILLAR LIGHT,
SOLAR LANDSCAPE LIGHT AND BIG POWER SOLAR GARDEN LIGHT.

IP65 CE RoHS





AC powered version

The lamp body is made of thickened die-cast aluminum, which has high strength, strong impact resistance and good corrosion resistance.

Power supply with voltage 220-240V

The light source uses 2 modules LEDs to achieve unifor m distribution of light and greatly improve the lighting effect.







Solar powered version

The lamp body is made of thickened die-cast aluminum, which has high strength, strong impact resistance and good corrosion resistance.

High-efficiency monocrystalline solar panels, power up to 20W.

Built-in LiFePO4 battery, capacity 20000MAH, long lifespan and safe.



Color temperature data-AC powered version



6500K/White light




3000K/Warm white

Lumen

3000K:
Luminous flux:3118.58lm Color rendering index:78.84Ra

6500K:
Luminous flux:3346.24lm Color rendering index:81Ra

Light distribution curve



TYPE:

The 220V voltage is mainly used in environments without sunlight, such as being shaded by trees, houses, etc., and buildings that bl ock sunlight, resulting in short charging time and unable to achiev e normal battery life and lighting time.

Color temperature data-Solar powered version



6500K/White light



3000K/Warm white

Lumen

3000K:
Luminous flux:1150lm Color rendering index:78.84Ra

6500K:
Luminous flux:1270lm Color rendering index:81Ra

Light distribution curve



TYPE:

This light type is mainly used in villa gardens, parking areas, park squares, community scenic spots, villa courtyards, and modern architectural lighting environments. 360-degree light, the lamp is suitable for installation height of 2.5~5 meters.

Parameter–AC powered version

Item +	
AC Garden light	TYD–2705
Specification +	
Light source	3030 SMD LED chip
LED Chip quantity（pcs）	80pcs
Material	Die–casting aluminum+PC lampshade
Lamp color	Black（Other colors can be customized）
Net weight（kg）	3.98kg
Product size(mm)	ϕ480mm x 78mm x H410mm
Installation diameter（mm）	ϕ76mm
Installation height	2.5m–5m

Parameter+	
Rated power（W）	30W
Input voltage（V）	AC220–240V
Color temperature	3000K – 6500K
Lumen（lm）	3118.58lm (3000K)、3346.24lm (6500K)
Color rendering index	CRI > 81
Beam angle	180°
Rated frequency	50Hz
waterproof level	IP65

Working environment+	
Operating temperature	–25℃~ 50℃
Working humidity	10%–90%

Parameter–Solar powered version

Item+	
Solar garden light	TYD–2705
Specification+	
Monocrystalline solar panel（W）	20W / 5V
Battery （MAH）	3.2V / 20000mAh
Light source	2835 SMD LED chip
LED Chip quantity（pcs）	80pcs
Material	Die–casting aluminum+PC lampshade
Lamp color	Black（Other colors can be customized）
Net weight（kg）	5.32kg
Size（mm）	ϕ480mm x 78mm x H410mm
Installation diameter（mm）	ϕ76mm
Installation height	2.5m–5m
Parameter+	
Rated power（W）	20W
Input voltage（V）	DC 3.2V
Color temperature(K)	3000K – 6500K
Lumen（lm）	1150lm (3000K)、1270lm (6500K)
Color rendering index	CRI > 80
Working hours （Lighting sensor）	12hours （3~5 rainy days）
Waterproof level	IP65
Beam angle	180°


Working environment+	
Operating temperature	–25℃~ 50℃
Working humidity	10%–90%

Lamp size diagram






Packaging Information



LED garden light*1



Inner foam



Outer box

Version	Package	Quantity	Carton quantity	Carton size（mm）	Net weight kg	Gross weight kg
Solar powered	Inner box	/	/	/	/	/
	Outer box	1	1	485 x 485 x 240	5.32	6.44
AC powered	Inner box	/	/	/	/	/
	Outer box	1	1	485 x 485 x 240	3.98	5.02

Gross and net weights are for reference only

Lighting Features




Thick die-cast aluminum

One-piece molding, high strength and rigidity



Design principle

Inspired by the appearance of the moon in the water clover design




IP65 waterproof level

No fear of wind and rain, normal lights on rainy days




lamp details



Monocrystalline solar panel

Efficient conversion of photovoltaic panels, which can quickly absorb energy and charge normally in rainy weather



PC optical lens


Wide irradiated area, light transmittance up to 90%





High lumen 2835 chip

High-power LED chip, bright light, lifespan can reach 80,000-100,000 hours




LiFePO4 battery

Built-in 20AH large-capacity battery, high safety performance, long lifespan, more than 2000 charge and discharge cycles, fast charging rate



Push-button waterproof switch

After turning on the switch, you need to wait for 10s
(Solar lights need to be turned on in the dark)



Thick die-cast aluminum

All-aluminum lamp body,waterproof and durable
Put it into the light pole and fix it with 4 hexagonal screws, the inner diameter is 76mm

Water Moon/
Courtyard Lighting

TYPE: This light type is mainly used in villa gardens, parking areas, park squares, community scenic spots villa co urtyards and modern architectural lighting environme nts.180-degree light, the lamp is suitable for installat ion height of 2.5~5 meters.




Odins gate


XY 28554













